

## Description

METHOD FOR THE COMPENSATION OF INTERFERENCE IN A SIGNAL  
GENERATED BY DISCRETE MULTITONE MODULATION, AND CIRCUIT  
5 ARRANGEMENT FOR CARRYING OUT THE METHOD

FIELD OF INVENTION

The invention relates to a method for the compensation  
of interference in a signal generated by discrete  
10 multitone modulation ~~according to the preamble of~~  
~~patent claim 1, and to a circuit arrangement for~~  
~~carrying out the method according to the preamble of~~  
~~patent claim 4.~~

15 BACKGROUND

Discrete multitone modulation (DMT) - also called  
multicarrier modulation - is a modulation method which  
is suitable in particular for the transmission of data  
via channels effecting linear distortion. Compared with  
20 a so-called single-carrier method - for example  
amplitude modulation - which has only one carrier  
frequency, a multiplicity of carrier frequencies are  
used in discrete multitone modulation. Each individual  
carrier frequency is modulated in amplitude and phase  
25 according to the quadrature amplitude modulation (QAM).  
A multiplicity of QAM-modulated signals are thus  
obtained. In this case, a specific number of bits can  
be transmitted per carrier frequency. Discrete  
multitone modulation is used for example for digital  
30 audio broadcasting DAB under the designation OFDM  
(Orthogonal Frequency Division Multiplex) and for the  
transmission of data via telephone lines under the  
designation ADSL (Asymmetric Digital Subscriber Line).

35 In ADSL, the physical transmission channel is a two-  
wire line (copper double core) of the telephone  
network. However, such a transmission channel has a  
long transient recovery time. Signals generated by

discrete multitone modulation typically contain very short pulses having a high amplitude, which effect impulse responses that decay slowly in this transmission channel. If an impulse response has still  
5 not completely decayed when a new pulse arrives at the receiver, then interference occurs in the receiver. For compensation of such interference, DMT receivers contain time domain equalizers, for example, which are intended to shorten the impulse response of the  
10 transmission channel and avoid interference on account of superposition of an impulse response of a pulse that has not yet decayed and an impulse response of a subsequent pulse.

15 The time domain equalizer (TDEQ) may be embodied for example as a digital transversal filter whose coefficients are adjustable. The design of such time domain equalizers is described in Al-Dhahir, N., Cioffi, J.M., "Optimum Finite-Length Equalization for  
20 Multicarrier Transceivers", IEEE Trans.on Comm., Vol. 44, No. 1, Jan. 1996.

The document US-A-5 521 908 describes a method for determining a set of time domain parameters of an SIRF  
25 filter. To that end, the original channel and echo impulse responses are determined to an approximation and recorded on SIRF coefficients based on the combined channel and echo impulse responses that have been calculated to an approximation. An SSNR ratio is  
30 calculated for the SIRF coefficients, the individual steps being repeated for determining the coefficients with the best SSNR ratio.

The document EP 0 768 778 A1 comprises a method and a  
35 corresponding apparatus for the transmission of impulse responses. A set of parameters is calculated for an equalizer, which equalizes an impulse response in such a way that the equalized impulse response corresponds,  
to an approximation, to a desired impulse response of a

predetermined length. To that end, an error function is minimized by means of eigenvalue and eigenvector calculation of a channel-dependent matrix. The channel-dependent matrix comprises a signal, a disturbed  
5 signal, a desired impulse response length and a desired impulse response delay. The error function has a first component, which represents the difference between an equalized impulse response and the desired impulse response, and a second component, which represents the  
10 energy transmitted in unused frequency bands. The eigenvector associated with the minimum eigenvalue of the channel-dependent matrix represents the set of equalizer parameters.

15 What is disadvantageous with such time domain equalizers, however, is the high number of coefficients of the digital transversal filter used as time domain equalizer, and the complex adaptation of the digital transversal filter. Given a filter length of 20 to 40  
20 coefficients, approximately 50 to 100 million multiplications have to be carried out per second. Accordingly, a digital filter for time domain equalization requires a very high computing power. In addition, each coefficient has to be adjusted for the  
25 adaptation of the digital transversal filter. This requires a long adaptation time which has to be provided at the beginning of an ADSL transmission.

#### SUMMARY

30 The technical problem on which the invention is based resides, therefore, in specifying a method for the compensation of interference in a signal generated by discrete multitone modulation and a circuit arrangement for carrying out the method, wherein the method is  
35 simple to perform and the circuit arrangement is simple to produce and complex adaptation of coefficients is not necessary.

~~This problem is solved by means of a method for the~~

~~compensation of interference in a signal generated by discrete multitone modulation having the features of patent claim 1 and by means of a circuit arrangement for carrying out the method having the features of patent claim 4. Advantageous refinements emerge from the respective subclaims.~~

The invention relates to a method for the compensation of interference in a signal generated by discrete multitone modulation. The interference is essentially caused by the transient process of a transmission channel via which the signal is transmitted. The signal has a multiplicity of symbols and each symbol is preceded by a cyclic prefix. A multiplicity of parameters are calculated from the digitized samples of the signal. The transient process of the transmission channel is in turn calculated to an approximation from the multiplicity of parameters. For compensation of the interference, the transient process calculated to an approximation is subtracted from the digitized samples. Advantageously, the multiplicity of parameters are calculated directly from the signal and there is no need for time-consuming adaptation of coefficients as in the case of time domain equalizers. Consequently, convergence problems, caused by excessively long adaptation, cannot occur either. In this case, the transient process calculated to an approximation results from the consideration that the transmission channel behaves like a low-order linear system and the transient process of such a system can be calculated very simply. Advantageously, the transient process calculated to an approximation can be subtracted from the digitized samples in the time domain or in the frequency domain. In the event of subtraction in the frequency domain, Fourier transformation of the transient process calculated to an approximation is not necessary since the coefficients multiplied by exponential functions defining the transient process remain the same. In a preferred embodiment, each

parameter is calculated by subtraction of a pair of digitized samples. In this case, it is particularly preferred for each pair of digitized samples to have a digitized sample of a symbol and a digitized sample of a cyclic prefix.

The invention furthermore relates to a circuit arrangement for carrying out a method for the compensation of interference in a signal generated by discrete multitone modulation. The signal has a multiplicity of symbols and each symbol is preceded by a cyclic prefix. In this case, digitized samples of the signal are fed to a serial/parallel converter. Furthermore, a multiplicity of subtractor circuits are provided. Each subtractor circuit subtracts a digitized sample of the symbol from a corresponding digitized sample of the cyclic prefix preceding the symbol. The result of the subtraction is an interference superposed on the digitized sample of the cyclic prefix. For each coefficient of the equation which was set up for calculating the transient process of the transmission channel to an approximation, multiplier circuits are provided which multiply the output signal of each subtractor circuit by the coefficients. The output signal of each multiplier circuit is then subtracted from the corresponding digital sample of the symbol.

Further advantages, features and possible applications of the invention emerge from the following description of exemplary embodiments in conjunction with the drawing, in which

#### **BRIEF DESCRIPTION OF FIGURES**

figure 1 shows a block diagram of the method for the compensation of interference in a signal generated by discrete multitone modulation; and

figure 2 shows an exemplary embodiment of a circuit

arrangement for carrying out the method for the compensation of interference in a signal generated by discrete multitone modulation; and

5

figure 3 shows a block of the signal generated by discrete multitone modulation.

#### **DETAILED DESCRIPTION**

10 Figure 1 illustrates a block diagram with the components essential to the invention and three different exemplary embodiments of the method, which are represented by broken lines. The block diagram illustrated corresponds to a receiver for a signal  
15 generated by discrete multitone modulation.

An analog reception signal which has been generated by discrete multitone modulation is fed to an analog-to-digital converter 1. The analog-to-digital converter 1  
20 samples the analog reception signal and converts the samples of the analog reception signal into digital values.

A block of the signal generated by discrete multitone modulation is illustrated in figure 3. In this case, a  
25 number  $N+P$  of digital values form the block, which contains a transmitted symbol comprising  $N$  digital values. The remaining  $P$  digital values of the block correspond to the last  $P$  digital values of the symbol  
30 and form a cyclic prefix. The cyclic prefix is situated at the start of the block. The cyclic prefix generates a "pseudo-periodicity" which enables easier frequency domain equalization of the received signal for the receiver. This is because the transmission channel can  
35 be regarded as a linear transfer function.

As illustrated in figure 1, the digital values of the block are fed to a unit for removing the cyclic prefix 2, on the one hand, and to a compensation unit for

parameter calculation 3, on the other hand.

The compensator unit for parameter calculation 3 calculates from the cyclic prefix interference brought about by the transient process of, in particular, the transmission channel. To that end, the corresponding digital values of the cyclic prefix and of the symbol are subtracted from one another. The result of the subtraction corresponds to the interference. This holds true, of course, only if the impulse response of the transmission channel is shorter than the time duration of a symbol including cyclic prefix. In this case, the digital values at the end of a block can be regarded as having settled and being free from errors. This means that interference on account of the transient process can be calculated very accurately. From this interference, the compensator unit 3 calculates parameters for a linear equation which specifies the transient process, which essentially causes the interference, to an approximation.

The linear equation for calculating the transient process to an approximation is based on the assumption that the transient process behaves like the transient process in a low-order linear system. In this case, first- and second-order systems have proved to be sufficient. In a second-order system taken as an example, the equation for calculating the transient process has two parameters  $c_1$  and  $c_2$ . The general form of the equation for calculating the transient process is represented by the following formula:

$$e(n \cdot T) = c_1 \cdot f_1(n \cdot T) + c_2 \cdot f_2(n \cdot T) + \dots$$

The functions  $f_i(n \cdot T)$  are exponential functions which may also be complex conjugate. By means of Z transformation, the following equation for calculating the transient process holds true in the frequency domain:

$$E(z) = c_1 \cdot F_1(z) + c_2 \cdot F_2(z) + \dots$$

Consequently, two digital values of the interference on  
5 account of the transient process are required for the  
calculation of two parameters  $c_1$  and  $c_2$ .

The calculated parameters can be fed to a unit for  
calculating the transient process 4, on the one hand,  
10 and to a unit for transformation into the frequency  
domain 5, on the other hand.

If the compensation of the interference takes place in  
the time domain, then the transient process calculated  
15 by the unit for calculating the transient process 4 is  
subtracted from the output values of the unit for  
removing the cyclic prefix 2 by means of a first  
subtractor 8. The error-free digital values thus  
calculated are then fed to a unit for calculating the  
20 fast Fourier transform 9 (FFT), which converts the  
signal represented by the digital values from the time  
domain into the frequency domain.

If, instead of this, the compensation of the  
25 interference is intended to take place in the frequency  
domain, the output values of the unit for  
transformation into the frequency domain 5 are  
subtracted from the output values of the unit for  
calculating the fast Fourier transform 9 by means of a  
30 second subtractor 10. The error-free digital values thus  
calculated are then fed to a frequency domain equalizer  
11 (FEQ = Frequency Equalization).

The frequency domain equalizer 11 is embodied as an  
35 adaptive digital filter whose coefficients are adapted  
to the transmission channel at the beginning of a  
transmission. If the frequency domain equalizer has  
been completely adapted, then the transfer function  
represents the inverse transfer function of the



transmission channel.

The adapted values of the digital filter of the frequency domain equalizer are fed to a unit for system analysis 6. The unit for system analysis 6 calculates, from the coefficients fed to it, the properties of the transmission channel and composes therefrom the equation for calculating the transient process of the transmission channel to an approximation. This equation is fed to the compensator unit for parameter calculation 3 and evaluated by the latter.

As a third alternative, the compensation of interference can take place after the frequency domain equalization by the frequency domain equalizer 11. To that end, the output values of the unit for transformation into the frequency domain 5 are fed to a unit for multiplication by the FEQ coefficients 7. The unit for multiplication by FEQ coefficients 7 multiplies the values fed to it by the adapted coefficients of the frequency domain equalizer 11. The output values of the unit for multiplication by FEQ coefficients 7 are then subtracted from the output values of the unit for frequency domain equalization 11 by means of a third subtractor 12.

Finally, the interference-free digital values thus calculated are fed to a unit for decision and decoding 13, which generates a digital signal containing the information contained in the analog reception signal.

Figure 2 illustrates an exemplary embodiment of a circuit arrangement for carrying out the method.

In this exemplary embodiment, the compensation of the interference takes place in the time domain before fast Fourier transformation.

An analog reception signal is fed to an analog-to-

digital converter 14 which converts the analog reception signal fed to it into digital values.

5 The digital values at the output of the analog-to-digital converter 14 are fed to a unit for serial/parallel conversion 15.

10 The unit for serial/parallel conversion 15 has N+P storage locations for digital values. N+P digital values form exactly one block of the signal generated by discrete multitone modulation. In this case, a block has, at the start, the cyclic prefix comprising P digital values, and following that the symbol comprising N digital values.

15 In this exemplary embodiment, the transmission channel is regarded as a first-order system, only one digital value of the interference being required to calculate the transient process.

20 Assuming that the transient process of the channel has already decayed before the last digital value of a block (storage locations 1, 2) the error on account of the transient process is calculated by subtraction of the last digital value of the block (storage location 25 1) and the last digital value of the cyclic prefix (storage location N+1).

30 To that end, these digital values are fed to a subtractor 16. The calculated error at the output of the subtractor 16 is in each case fed to each each multiplier 17, 18. In this case, one multiplier is provided for each of the N digital values of the symbol. Each multiplier 35 multiplies the error at the output of the subtractor 16 by a parameter which has been calculated by means of the system equation for a first-order linear system. The calculated transient process is in each case subtracted from a digital value of the symbol by means

of subtractors 19, 20.

The digital values of the symbol that have thus been calculated and corrected are then fed to a unit for  
5 fast Fourier transformation 21, which converts the signal represented by the digital values fed to it from the time domain into the frequency domain for further processing.